



mini66 BEARING ISOLATOR

IP-66 Performance From A Bearing Isolator This Small?



ONLY FROM INPRO/SEAL.

Permanent bearing protection now comes in small packages.

Introducing the Inpro/Seal® mini66™ Bearing Isolator. The mini66 Bearing Isolator is rated IP66, permanently protecting against both dust and water ingress. With a 9.52 mm [0.375 in] overall length, the mini66 is the smallest IP66 rated Bearing Isolator available.

It's unique design exceeds IEEE-841 standards and is a perfect fit for washdown environments. Manufactured in bronze and stainless steel, the mini66 Bearing Isolator is custom engineered to meet your specifications.

Count on us to improve reliability, increase MTBR, and maximize asset protection and utilization. As the inventor and global leader of Bearing Isolator technology, Inpro/Seal has the knowledge and local sales network to deliver expert engineering and proven results. Same day shipments available.

ADVANTAGES

Inpro/Seal mini66™ Bearing Isolators:

- Provide permanent bearing protection to applications with limited space.
- Are IP66 rated, protecting against both dust and water ingress.
- Have a 9.52 mm [0.375 in] overall length, making it the smallest IP66 rated Bearing Isolator on the market.
- Can be manufactured in bronze and stainless steel.
- Are custom engineered to meet the exact specifications of your application.
- Can be shipped the same day an order is placed.



www.inpro-seal.com | info@inpro-seal.com

